

STRUCTURE GUARD™-RS



# STRUCTURE GUARD™-RS SAFETY DATA SHEET

PART A



**REPAIR  
MATERIALS**

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	Structure Guard™-RS - Part A
Revision Date	11-2018
Product Code	Rapid Set Epoxy
Company	Stag Technologies, 564 W. 9320 S., Sandy, UT 84070
Company Contact	Matthew Peterson
Company Phone	844-STAGTEC
Emergency	800-535-5053

## 2. HAZARDS IDENTIFICATION

GHS Ratings:	
Carcinogen	2 - Limited evidence of human or animal carcinogenicity
GHS Hazards:	
H351	Suspected of causing cancer
GHS Precautions:	
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P281	Use personal protective equipment as required
P308+P313	If exposed or concerned: Get medical advice/attention
P405	Store locked up
P501	Dispose of contents/container to ...
Signal Word	Warning



### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Cass #	Weight Concentration %
Epoxy Resin	25085-99-8	80.10%
Barium Sulfate	7727-43-7	10.00% - 20.00%
Titanium Dioxide	13463-67-7	5.00% - 10.00%
Silica	67762-90-7	1.00% - 5.00%

### 4. FIRST AID MEASURES

If inhaled remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms. Rinse immediately with plenty of water for at least 15 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue Rinsing. Get medical attention, if irritation or symptoms of overexposure persists. Immediately wash skin with soap and plenty of water. If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

### 5. FIRE FIGHTING MEASURES

Flash Point	N/A
LEL	N/A
UEL	N/A

Not applicable  
 Foam, Carbon dioxide (CO<sub>2</sub>) or dry chemical or water spray (water stream may be ineffective) .  
 No information available  
 Not available  
 Firefighters, and others exposed, wear self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

Stop leak. Dike or contain spill. Pump into slavage tanks and/or absorb with suitable material. Use sparkless shovel to remove material. Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use appropriate containment and clean up immediately. Stop leak, Dike and contain spill. Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.

### 7. HANDLING AND STORAGE

Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Keep away from heat and flame. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Avoid exposure to heat, light, and air for prolonged periods of time. Store in a cool, dry well ventilated area away from sources of heat and incompatible materials. Eliminate all ignition materials and incompatible materials. Collect spill with non spark tools. No information available.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Epoxy Resin 25085-99-8	Not Established	Not Established	Not Established
Barium Sulfate 7727-43-7	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)	5 mg/m <sup>3</sup> TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)
Titanium Dioxide 13463-67-7	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	Not Established
Silica 67762-90-7	Not Established	Not Established	Not Established

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended. Always use adequate ventilation that comply with local regulations.

### Eye/face Protection:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

### Skin Protection:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

### Respiratory Protection:

A NIOSH air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known or any other circumstance where air purifying respirator may not provide adequate protection.

## 9. PHYSICAL & CHEMICAL PROPERTIES

Boiling Range	2500 to 3000 °C
Specific Gravity (SG)	1.348
Lbs VOC/Gallon Less Water	0.00
Lbs VOC/Gallon Less Exempt	0.00
% VOL by Volume	0.00

## 10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stable, Hazardous polymeraization will not occur. STABLE. Strong acids, caustics, oxidixers, Avoid uncontrolled exposure to Epoxy Resin, Amine.

No Data Found

None known, other than Sec. #2 and Sec #5

No Data Found

Hazardous polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

Mixture Toxicity:

Component Toxicity

Eyes Respiratory System

Effects of Overexposure:

CAS Number 13463-67-7

Description Titanium Dioxide

% Weight 5 to 10%

Carcinogen Rating Titanium Dioxide: NIOSH: potential occupational carcinogen

IARC: Possible human carcinogen

OSHA: listed

Avoid breathing vapors

Oral N.D.A.

Dermal N.D.A.

Inhalation N.D.A.

## 12. ECOLOGICAL INFORMATION

No ecotoxicity data was found for the product

Component Ecotoxicity

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

## 14. TRANSPORT INFORMATION

UN3082 Enviromentally Hazardous Substance, Liquid N.O.S. (Epoxy Resin)

Packaging Group III Hazardous Class 9

## 15. REGULATORY INFORMATION

OSHA:29 CFR

1910.1200 Haxardous

Chemical "Irritant", Sensitizer

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

13463-67-7	Titanium Dioxide	5 to 10 % Carcinogen
------------	------------------	----------------------

The following chemicals are classified under SARA 313 Toxic Release Inventory (TRI):

- None

Country	EU
Regulation	REACH (EU) SUBSTANCES OF VERY HIGH CONCERN Toxic Substance Control Act (TSCA)
All Components Listed	EU - No TSCA - Yes
Safety Phrase	None

**16. OTHER INFORMATION**

Further information	HMIS® is a registered trade and service mark of the NPCA.
HMIS® ratings	Health: 1 Flammability: 0 Physical hazard: 1 Personal Protection: B
NFPA ratings	Health: 1 Flammability: 0 Instability: 0