

STRUCTURE GUARD™-RS



STRUCTURE GUARD™-RS SAFETY DATA SHEET

PART B



**REPAIR
MATERIALS**

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	Structure Guard™-RS - Part B
Revision Date	11-2018
Product Code	Rapid Set Epoxy
Company	Stag Technologies, 564 W. 9320 S., Sandy, UT 84070
Company Contact	Matthew Peterson
Company Phone	844-STAGTEC
Emergency	800-535-5053

2. HAZARDS IDENTIFICATION

GHS Ratings:

Skin sensitizer	1	Skin sensitizer
Reproductive toxin	2	Human or animal evidence possibly with other information

GHS Hazards:

H317	May cause an allergic skin reaction
H361	Suspected of damaging fertility or the unborn child

GHS Precautions:

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see ... on this label)
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up
 P501 Dispose of contents/container to ...
 Signal Word Warning



3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Barium Sulfate	7727-43-7	10.00% - 20.00%
Silica	67762-90-7	1.00% - 5.00%

4. FIRST AID MEASURES

If inhaled remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms. Rinse immediately with plenty of water for at least 15 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue Rinsing. Get medical attention, if irritation or symptoms of overexposure persists. Immediately wash skin with soap and plenty of water. If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flash Point	N/A
LEL	N/A
UEL	N/A
Not applicable	
Foam, Carbon dioxide (CO ₂) or dry chemical or water spray (water stream may be ineffective) .	
No information available	
Not available	
Firefighters, and others exposed, wear self-contained breathing apparatus.	

6. ACCIDENTAL RELEASE MEASURES

Stop leak. Dike or contain spill. Pump into slavage tanks and/or absorb with suitable material. Use sparkless shovel to remove material. Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use appropriate containment and clean up immediately. Corrosive. Avoid personal contact and breathing vapor or mist. Stop leak. Dike and contain spill. Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.

7. HANDLING AND STORAGE

Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Keep away from heat and flame. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Avoid exposure to heat, light, and air for prolonged periods of time. Store in a cool, dry well ventilated area away from sources of heat and incompatible materials. Eliminate all ignition materials and incompatible materials. Collect spill with non spark tools.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Barium Sulfate 7727-43-7	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	5 mg/m ³ TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)
Silica 67762-90-7	Not Established	Not Established	Not Established

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended systems are not effective wear suitable personal protective equipment, which preforms satisfactory and meets OSHA or other recognized standards. Consult with local procedures for selection, training, and maintenance of the personal protective equipment. Always use adequate ventilation that comply with local regulations.

Eye/face Protection:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

Skin Protection:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

Respiratory Protection:

A NIOSH air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known or any other circumstance where air purifying respirator may not provide adequate protection.

9. PHYSICAL & CHEMICAL PROPERTIES

Specific Gravity (SG)	1.299
Lbs VOC/Gallon Less Water	0.00
Lbs VOC/Gallon Less Exempt	0.00
% VOL by Volume	0.00

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stable, Hazardous polymerization will not occur. Will react with Epoxy Resins especially at elevated temperatures. STABLE.

Epoxy Resins under uncontrolled conditions. Mineral acids. Organic acid, oxidizers, Reacts with metals until reacted with epoxy. None known.

Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity:

Component Toxicity:

Eyes	Irritant to the eyes. Corrosive to Eyes
Skin	Irritant to the skin. Corrosive to Skin
Inhalation	Irritant to respiratory tract. Prolonged or excessive inhalation may cause respiratory tract irritation.
Sensitization	Skin sensitization in humans. Avoid breathing vapors.
Eyes	Respiratory System

Effects of Overexposure

Avoid breathing vapors

Oral	N.D.A.
Dermal	N.D.A.
Inhalation	N.D.A.

12. ECOLOGICAL INFORMATION

No ecotoxicity data was found for the product.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

14. TRANSPORT INFORMATION

UN2735 Amines, Liquid, corrosive, n.o.s. (Benzene-1,3-Dimethanamine, 1,5-Pentanediamine, 2-Mthyl).

DOT Hazard Class 8 DOT Packaging Class II

15. REGULATORY INFORMATION

OSHA:29 CFR 1910.1200 (40 CFR 372.65)	Hazardous Chemical "Irritant", Sensitizer Supplier Notification Required
TSCA	Ingredients listed
SARA III	Sec311 & 312 Immediate Health Hazard; Sec313 Chemicals above de minimus level: None

CA PROP. 65 NOTICE WARNING

CANADIAN REGULATORY INFO	WHMIS; Hazard Classification: D2B Skin Sensitizer. Refer to SDS for specific warnings
WHMIS Symbols	Stylized T.
WHMIS Trade Secret Registry Numbers	None
Hazardous Products Act Informtion	This product SDS contains ingredients which are Controlled and/or on the Ingredient Disclosure List (HPA sections 13 and 14).

Country	EU
Regulation	REACH (EU) SUBSTANCES OF VERY HIGH CONCERN Toxic Substance Control Act (TSCA)
All Components Listed	EU - No TSCA - Yes
Safety Phrase	None

16. OTHER INFORMATION

Further information	HMIS® is a registered trade and service mark of the NPCA.
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 1 Personal Protection: G NFPA ratings Health: 3 Flammability: 0 Instability: 1