



FLEX GUARD™-FM SAFETY DATA SHEET

PART B



**REPAIR
MATERIALS**

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	FLEX GUARD-FM PART B
Revision Date	01-2019
Product Code	RE2120 B
Company	Stag Technologies, 564 W. 9320 S., Sandy, UT 84070
Company Contact	Matthew Peterson
Company Phone	844-STAGTEC
Emergency	Domestic Shipments and to Canada: 1-800-633-8253 International Shipments: 1-801-629-0667

2. HAZARDS IDENTIFICATION

GHS Ratings:		
Inhalation Toxicity	Acute Tox. 4	Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >=2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Reproductive toxin	1B	Presumed, Based on experimental animals
GHS Hazards		
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H360	May damage fertility or the unborn child	
GHS Precautions		
P201	Obtain special instructions before use	
P202	Do not handle until all safety precautions have been read and understood	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray	

P264	Wash ... thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Specific treatment (see ... on this label)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists, get medical advice/attention
P405	Store locked up
P501	Dispose of contents/container to ...
Signal Word	Danger



3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Proprietary Blend-29 C.F.R. 1910.1200(i).	872-50-4	20.00% - 30.00%
Barium Sulfate	7727-43-7	10.00% - 20.00%
Silica	67762-90-7	1.00% - 5.00%

4. FIRST AID MEASURE

If inhaled remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms. Rinse immediately with plenty of water for at least 15 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists. Immediately wash skin with soap and plenty of water. If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flash Point	96°C (205°F)
LEL	N/A
UEL	N/A

Not applicable

Foam, Carbon dioxide (CO2) or dry chemical or water spray (water stream may be ineffective) .

No information available

Not available

Firefighters, and others exposed, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Stop leak. Dike or contain spill. Pump into slavage tanks and/or absorb with suitable material. Use sparkless shovel to remove material. Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use appropriate containment and clean up immediately. Corrosive. Avoid personal contact and breathing vapor or mist. Stop leak, Dike and contain spill. Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.

7. HANDLING AND STORAGE

Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Keep away from heat and flame. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Avoid exposure to heat, light, and air for prolonged periods of time. Store in a cool, dry well ventilated area away from sources of heat and incompatable materials. Eliminate all ignition materials and incompatible materials. Collect spill with non spark tools. No information available.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Chemical Name / CAS No.	Proprietary Blend-29 C.F.R. 1910.1200(i). 872-50-4
OSHA Exposure Limits	Not Established.
ACGIH Exposure Limits	Not Established.
Other Exposure Limits	Not Established.

Chemical Name / CAS No.	Barium Sulfate 7727-43-7
OSHA Exposure Limits	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
ACGIH Exposure Limits	5 mg/m ³ TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)
Other Exposure Limits	NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)

Chemical Name / CAS No.	Silica 67762-90-7
OSHA Exposure Limits	Not Established.
ACGIH Exposure Limits	Not Established.
Other Exposure Limits	Not Established.

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended Always use adaquate ventilation that comply with local regulations.

Eye/face Protection	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face rotection reulation, or the Europena.
Skin Protection	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection	A NIOSH air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne.

9. PHYSICAL & CHEMICAL PROPERTIES

Boiling Range	202°C
Specific Gravity (SG)	1.184
Lbs VOC/Gallon Less Water	0.00
Lbs VOC/Gallon Less Exempt	0.00
% VOL by Volume	0.00

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stable, Hazardous polymeraization will not occur. Will react with Epoxy Resins especially at elevated temperatures. STABLE. Epoxy Resins under uncontrolled conditions. Mineral acids. Organic acid, oxidixers, Reacts with metals until reacted with epoxy. None known. Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity	Inhalation Toxicity LC50: 12mg/L
Component Toxicity	872-50-4 Oral LD50: 3,914 mg/kg (Rat) Dermal LD50: 8 g/kg (Rabbit) Inhalation LC50: 3 mg/L (Rat)
Eyes	Irritant to the eyes. Corrosive to Eyes
Skin	Irritant to the skin. Corrosive to Skin
Inhalation	Irritant to respiratory tract. Prolonged or excessive inhalation may cause respiratory tract irritation.
Sensitization	Skin sensitization in humans.
Effects of Overexposure	
Avoid breathing vapors	
CAS Number	None
Description	None
% Weight	None
Carcinogen Rating	None
Oral	N.D.A.
Dermal	N.D.A.
Inhalation	N.D.A.

12. ECOLOGICAL INFORMATION

No ecotoxicity data was found for the product.

Component Ecotoxicity

Proprietary Blend-29 C.F.R. 1910.1200(i).	96 Hr LC50 Lepomis macrochirus: 832 mg/L [static]; 96 Hr LC50 Pimephales promelas: 1072 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 1400 mg/L [static] 48 Hr EC50 Daphnia magna: 4897 mg/L 72 Hr EC50 Desmodesmus subspicatus: >500 mg/L
--	---

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

14. TRANSPORT INFORMATION

UN2735 Amines, Liquid, corrosive, n.o.s. (Benzene-1,3-Dimethanamine,1,5-Pentanediamine, 2-Mthyl).
DOT Hazard Class 8
DOT Packaging Class II

15. REGULATORY INFORMATION

OSHA:29 CFR 1910.1200 Haxardous Chemical "Irritant", Sensitizer
 OSHA:29 CFR 1910.1200 Haxardous Chemical "Irritant", Sensitizer
 (40 CFR 372.65) Supplier Notification Required

TSCA Ingredients listed
 SARA III Sec311 & 312 Immediate Health Haxard; Sec313 Chemicals above de minimus level: None

CA PROP. 65 NOTICE WARNING: CANADIAN REGULATORY INFORMATION
 WHMIS; Hazard Classification: D2B Skin Sensitizer. Refer to SDS for specific warnings

WHMIS Symbols Stylized T.

WHMIS Trade Secret Registry Numbers None

Hazardous Products Act Informtion This product SDS contains ingredients which are Controlled and/or on the Ingredient Disclosure List (HPA sections 13

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: 872-50-4 Proprietary Blend-29 C.F.R. 1910.1200(i). 20 to 30 % Carcinogen

The following chemicals are classified under SARA 313 Toxic Release Inventory (TRI):
 872-50-4 Proprietary Blend-29 C.F.R. 1910.1200(i). 20-30%

Country EU
 Safety Phrase None

Regulation All Components Listed
 REACH (EU) SUBSTANCES OF VERY HIGH CONCERN No
 Toxic Substance Control Act (TSCA) No

16. OTHER INFORMATION

Further information HMIS® is a registered trade and service mark of the NPCA.
 HMIS® ratings Health: 3
 Flammability: 1
 Physical hazard: 0

NFPA ratings Health: 3
 Flammability: 1
 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification, The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.