 **Quad-Cure® CIPP**  
**Lining System**  
BY VORTEX

# QUAD-CURE® CIPP LINING SYSTEM

TURN-KEY EQUIPMENT, LINER AND  
RESIN SYSTEM FOR TOTAL PIPE  
REHABILITATION

FEATURING QUAD-CURE®:

- CIPP LINING TRAILER
- RESINS
- LINERS



**REPAIR  
MATERIALS**





## Quadex® Presents the Quad-Cure® CIPP Lining System

Delivering proven infrastructure rehabilitation products and equipment for **more than 30 years**, the Quad-Cure CIPP Lining Trailer is the latest addition to the extensive line-up of industry leading equipment, complementing the **Quad-Cure resins and liners**, to offer a complete system.



Rear ramp door for easy transport of equipment and materials

### STANDARD CIPP TRAILER PACKAGE

QUANTITY	DESCRIPTION
1	Aluminum or Steel Frame Trailer with 7,000 lb. Axles
1	High Traction Floors
1	Covered and Insulated Walls and Ceiling
1	13,500 BTU Roof Mounted Dual A/C with Heat Strip
3	Overhead 36" Aluminum Storage Cabinet
2	Control Room LED Ceiling Mounted Lights
4	110V Electrical Receptacle Outlets
2	12V Receptacle/Charger
1	120V Forced Air Heater
1	50 Amp Converter Charger with Shore Plug and Cord
1	LED Ceiling Light
2	LED Ceiling Mounted Lights
6	110V Electrical Receptacle Outlets
1	Solid Wood Butcher Block Countertop
1	5 Drawer Tool Cabinet
1	Rear Back-up Camera
1	LED Directional Arrow Board
1	Roof Mounted Strobes
1	Commercial Grade Cummins® ONAN 7000 Generator
1	VanAir 80 CFM/110 PSI Air Compressor
1	Roof Mounted Solar Charging Package
1	Tread Plate Around Inside Base of Trailer
1	Stainless Steel Wetout Countertop
1	Single Drawer DBL Door Cabinet
1	Thermostatically Controlled Fridge/Freezer
1	Resin Bucket Rack
1	Spring Hinged Reinforced Ramp Door
1	Stereo System
1	High Vis Strobe Kit
2	Rear Mounted LED Flood Lights
1	CO2 Sensor
1	Hanging Curtain
1	Shocker Hitch
1	Fire Extinguisher
1	Regulated Air with 5 Drops





Side entry double door



High traction flooring with broad workspace and undercounter storage



Resin bucket rack keeps resin secure during transport



Control dashboard for lights, heat, A/C, stereo and more



E-Roller with grip coated brushless rollers, digital counter and foot pedal controller



Commercial grade Cummins® ONAN 7000 generator





Dual ceiling mounted A/C system for comfortable working environment during summer season



Vanair® 80 CFM/110 psi air compressor



Plenty of drawer space for 655 piece tool set



Ample overhead storage with locking cabinets



Solid wood workbench counter



Thermostatically controlled fridge/freezer

**QUAD-CURE® — STANDARD**

PRODUCT	DESCRIPTION	MIX RATIO	POT LIFE	WORK TIME
Quad-Cure® 4115	Epoxy	4 to 1	15 minutes	30 minutes
Quad-Cure® 4130	Epoxy	4 to 1	30 minutes	1 hour
Quad-Cure® 4160	Epoxy	4 to 1	60 minutes	2 hours
Quad-Cure® 3120	Epoxy	3 to 1	20 minutes	35 minutes
Quad-Cure® 3145	Epoxy	3 to 1	45 minutes	1 hour

**QUAD-CURE® LC — EXTENDED**

PRODUCT	DESCRIPTION	MIX RATIO	POT LIFE	WORK TIME
Quad-Cure® LC8	Epoxy	2 to 1	8 hours	N/A
Quad-Cure® LC30	Epoxy	6.6 to 1	30 hours	N/A

**QUAD-CURE® UV — ENVIRONMENTAL**

PRODUCT	DESCRIPTION	MIX RATIO	POT LIFE	WORK TIME
ULTRA-VIOLET: Quad-Cure® UV	Methacrylate	N/A	N/A	N/A

**QUAD-CURE® SF/SM/SS — QUICK**

PRODUCT	DESCRIPTION	MIX RATIO	POT LIFE	CURE TIME
Quad-Cure® SF	Silicate	2 to 1	8 minutes	35-40 minutes @ 60°F
Quad-Cure® SM	Silicate	2 to 1	20 minutes	60-105 minutes @ 60°F
Quad-Cure® SS	Silicate	2 to 1	30 minutes	180-240 minutes @ 60°F

**QUAD-CURE® LINERS****QUAD-CURE® LINER TUBE | STANDARD AND SCRIM REINFORCED**


Non-woven, needle punched polyester fiber capable of navigating sweeping bends.

**QUAD-CURE® LINER | FLEXIBLE LINER FAMILY**


Non-woven needle punched PE felt liner with choice of impermeable coatings design for transitions and navigating angles up to 90°.

**QUAD-CURE® LINER | NON-WOVEN**

Non-woven, circular looped PE, uniquely bonded to a seamless, impermeable polyurethane coating.

**QUAD-CURE® LINER CALTUBE LINER FAMILY**

Ultra-flexible, line of calibrated tubes that are extremely tear and temperature resistant, typically used for heat-cured installation. Available in a variety of colors.

**QUAD-CURE® LINER | PRELINER HOSE**

3-ply laminate tube combining two layers of linear LDPE and a high strength cord grid.



[WWW.VORTEXCOMPANIES.COM](http://WWW.VORTEXCOMPANIES.COM)

[SALES@VORTEXCOMPANIES.COM](mailto:SALES@VORTEXCOMPANIES.COM)

1-855-WHYDIG1

18150 IMPERIAL VALLEY DR.

HOUSTON, TX 77060

